

Secure Videoconferencing



VIDEO DYNAMICS
VDI-VTC-T2®
DUAL 55"
 (DUAL 55-80" FLAT PANELS OR 103"+
 FRONT PROJECTION
 OPTIONS AVAILABLE)

Designed for the IC executive office or small/medium sized conference room. Intuitive, compact, secure, and effective combined into a single application for Local Presentations and VTC. Utilizes the most advanced technologies to complete mission critical objectives and communications with TS/SCI Cleared Staff.



Superior video quality with the Tandberg PrecisionHD camera

MOBILITY OPTIONS



DESIGN FEATURES	APPLICATIONS	PERFORMANCE
<ul style="list-style-type: none"> Designed for SCIF spaces; executive offices and small/medium conference rooms Complete control through a single touch screen controller Large screen LED displays for easy viewing (optional front projection) Blu-Ray and HDTV viewing Low Power Consumption 	<ul style="list-style-type: none"> Presentation capabilities with integration to multiple PCs Videoconference with remote sites One touch control for most operations Command and Control Intelligence Analysis Real-Time Decision Making 	<ul style="list-style-type: none"> True HD Video supporting both 720P and 1080P Superior video quality using H.264 standards Real-Time operational feedback using touch screen controller Supports H.320 ISDN & H.323 IP Operates from Unclassified up to TS/SCI

Ask about our maintenance and support programs:

- 8x5 Parts and Labor
- 24x7 Parts and Labor
- 24x7 Telephone Support

Over 25 years of providing top shelf systems to the President, Intelligence Community and DoD.

VTC solutions that work for your business, no matter what your business might be.

(V) 703.709.8400
 (F) 703.709.5409
www.videodynamics.com



Secure Videoconferencing

VIDEO FEATURES

Native 16:9 widescreen
Side by Side or Full Screen
Viewing

MONITORS

Select from the following
monitor sizes:
55-80" LED
103"+ DLP FRONT
PROJECTION

VIDEO SOURCES

BluRay
Television Tuner
3 Digital PC Ports

VIDEO FORMATS

NTSC, VGA, SVGA, XGA,
WXGA, SXGA, HD720P,
HD1080P

SUPPORTED DISKS

Blu-Ray, DVD, DVD+R,
DVD+RW

SUPPORT TV

NTSC, ATSC, QAM

NETWORK INTERFACES

Integrated tray for a media
convertor
Standard: 1 x LAN /
Ethernet
Optional: 4 x ISDN BRI (RJ-
45); 1 x V.35/RS-449, RS-
366 Adtran

VTC BANDWIDTH

H.320 up to 512kbps
H.323 up to 2 Mbps

VTC VIDEO STANDARDS

H.261, H.263, H.263+,
H.263++ H.264, H.239
(DuoVideo)

CONTROL

Fully Integrated AMX
master controller; 10" Color
Touch Panel (12" shown)
Double Secured codec when
powered off

AUDIO

Stereo audio
PC Audio
15w + 15w (8 ohm)
Up to 2 Microphones

MAJOR COMPONENTS

Tandberg C Series Codec
Tandberg PrecisionHD Cam
LED Flat Panels with wall
mounts
AMX Micro Processor
controller
AMX Touch Screen Panel
BluRay Player
Contemporary Research HD
TV Tuner

INSTALLATION (Option)

Fully integrated with wall
mounted displays and
camera; AMX control panel
and microphones on
conference table via surface
mounted AV track (under
floor if CFE/GFE conduit is
provided)

FACILITY

Power and HVAC
requirements provided at
time of purchase

DOCUMENTATION AND TRAINING

Quick Start User's Guide
Up to 4 hours hands-on
training (NCR)

DIMENSIONS (WxHxD)

Equipment rack:
20 1/8 x 18 7/8 x 15 15/16

POWER—ON

Rack: 115W 120VAC
Monitor: 2 @ 190W 120VAC
(Based on 55" Monitors)

POWER—STANDBY

Rack: 70 watts excluding
displays
Monitor: 2 @ 5 watts LED
(Based on 55" Monitors)

VTC Network Certification

Assistance Provided

WARRANTY

1 Year Parts and Labor

ACCESSORIES/OPTIONS:

Professional Installation
Modular Mobile Cart
8x5 Maintenance (P&L, NBD)
24x7 Maintenance (P&L,
NBD, W/24x7 Telephone
Support)
Premium Resolution
MultiSite Option
Additional Microphones
KIV Encryption Support
MultiZone Digital Clock
VTC Support Furniture
Room Acoustical Paneling



Videoconferencing Systems
Broadcast TV Systems
Audio Visual Systems

VIDEO DYNAMICS, INC
14000A Thunderbolt Place
Chantilly VA 20151
Tel: 703.709.8400
Fax: 703.709.5409

<http://www.videodynamics.com>
E-mail: information@videodynamics.com